




Illustration image

RECOMMENDED ACCESSORIES

- TOOL BOX HBC
- IRON SEPERATOR
- H-Lock QUICK COUPLING SYSTEM
- CRUSH CONTROL
- DUST SUPPRESSION
- ROTATION METER
- BUCKET TEETH

HARTL CRUSHER Performance*



* The production capacities vary based on material, feed size and close side setting. Indicated capacities based on medium hard material crushed under optimal conditions and taking the swivel time into account.

- HBC 650
- HBC 750
- HBC 950
- HBC 1250

MODEL	HBC 750
Excavator weight t**	≥ 18
Inlet opening mm	750 x 500
Rotation rpm	350
Rated capacity acc. ISO 7451 m ³	0.73
Hydraulic motor cc	80
Max. sound power level dB(A)	L _{W,A} 110.5
Oil flow rate l/min	> 145
Oil pressure bar	220
CSS toggle STD/OPT mm	35-100/12-75
Toggle system	Up-thrust
Mainframe construction	HARDOX 450
Crushing unit	Cast iron
Greasing system	Central 1-point
IN/OUT acc. ISO 6162 (SAE J518c)	3/4" 6000 psi flange
DRAIN acc. ISO 6162 (SAE J518c)	1/2" 3000 psi flange
Length mm	2210
Width mm	1210
Height mm	1370
Weight kg	2800
Operation temperature °C	- 10 / + 60
HS Code	84742000
Warranty months	12

Right to alter technical information without notice reserved

** Always consult and obey your machines lifting capability guidelines to insure safe operation of the crusher.